



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS # : 081831

QUARTZ INEO HKS D 5W-30

Date of the previous version: 2013-02-11

Revision Date: 2015-03-31

Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	QUARTZ INEO HKS D 5W-30
Number	BQ4
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Motor oil.
------------------------	------------

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL LUBRIFIANTS 562 Avenue du Parc de L'île 92029 Nanterre Cedex Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71
-----------------	--

For further information, please contact:

Contact Point	HSE
E-mail Address	rm.msds-lubs@total.com

1.4. Emergency telephone number

+33 1 49 00 00 49 (24h/24, 7d/7)
 France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59
 In France : - PARIS : Hôpital Fernand Widal 200, rue du Faubourg Saint-Denis 75475 Paris Cédex 10 , Tel : 01.40.05.48.48. -
 MARSEILLE : Hopital Salvator, 249 bd Ste Marguerite 13274 Marseille cedex 5, Tel : 04.91.75.25.25. - LYON : Hopital Edouard
 Herriot, 5 place d'Arsonvol, 69437 Lyon cedex 3, Tel : 04.72.11.69.11. - NANCY : Hopital central, 29 Av du Mal De Lattre de
 Tassigny, 54000 Nancy, Tel : 03.83.32.36.36 ou le SAMU : Tel (15)

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008 ***

*For the full text of the H-Statements mentioned in this Section, see Section 2.2.****

Classification***

The product is classified as dangerous in accordance with Regulation (EC) No. 1272/2008***
 Serious eye damage/eye irritation - Category 2*** - (H319)***

DIRECTIVE 67/548/EEC or 1999/45/EC

Version EU



SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

For the full text of the R-phrases mentioned in this Section, see Section 16

The substance/mixture is non-dangerous in accordance with Directive(s) 67/548/EEC with amendments and/or 1999/45/EC with amendments

Symbol(s)

Not classified***

2.2. Label elements

Labelled according to

REGULATION (EC) No 1272/2008***

**Signal Word**

WARNING***

Hazard Statements ***

H319 - Causes serious eye irritation***

Precautionary Statements

P280 - Wear eye protection/ face protection***

2.3. Other hazards**Physical-Chemical Properties**

Contaminated surfaces will be extremely slippery.

Environmental properties

Should not be released into the environment.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS3.2. Mixture**Hazardous ingredients**

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Dir. 67/548)	Classification (Reg. 1272/2008)
Distillates (petroleum), hydrotreated heavy paraffinic***	265-157-1	01-2119484627-25	64742-54-7	<50	-	Asp. Tox. 1 (H304)
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)***	298-577-9	01-2119543726-33	93819-94-4	<2	Xi;R38-41 N;R51-53	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)
bis(nonylphenyl)amine***	253-249-4	01-2119488911-28	36878-20-3	<2	R53	Aquatic Chronic 4 (H413)

Version EU



SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

Ethyl acrylate***	205-438-8* **	01-2119459301-46** *	140-88-5	<0.00020	R11 R20 R21 R22 R36 R37 R38 R43***	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 3 (H331) Aquatic Chronic 3 (H412) Flam. Liq. 2 (H225) ***
-------------------	------------------	-------------------------	----------	----------	--	--

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.
Skin contact	Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact	Severely irritating to eyes.***
Skin contact	Not classified.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Version EU



SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

5.3. Advice for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Personal Protective Equipment See Section 8 for more detail.

Waste treatment See section 13.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Version EU

SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

Advice on safe handling	When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
Prevention of fire and explosion	Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a bonded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.
--	--

Materials to Avoid	Strong oxidizing agents.
---------------------------	--------------------------

7.3. Specific end uses

Specific use(s)	No information available.***
------------------------	------------------------------

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits	Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m ³ , NIOSH (REL) TWA 5 mg/m ³ , STEL 10 mg/m ³ , ACGIH (TLV) TWA 5 mg/m ³ (highly refined) Ingredients with workplace control parameters***
------------------------	---

Chemical Name	European Union
Ethyl acrylate*** 140-88-5	STEL 10 ppm STEL 42 mg/m ³ TWA 5 ppm TWA 21 mg/m ³ ***

Legend	See section 16
---------------	----------------

DNEL Worker (Industrial/Professional)***

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7				5.4 mg/m ³ /8h (aerosol - inhalation)

Version EU



SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** 93819-94-4			0.58 mg/kg Dermal 8.31 mg/m ³ Inhalation	
bis(nonylphenyl)amine*** 36878-20-3			0.62 mg/kg bw/day Dermal 4.37 mg/m ³ Inhalation	
Ethyl acrylate*** 140-88-5		0.92 mg/m ³ (dermal)***		21 mg/m ³ (inhalation)***

DNEL Consumer***

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7				1.2 mg/m ³ /24h (aerosol - inhalation)
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** 93819-94-4			0.29 mg/kg Dermal 2.11 mg/m ³ Inhalation 0.24 mg/kg Oral	
bis(nonylphenyl)amine*** 36878-20-3			0.31 mg/kg bw/day Dermal 1.09 mg/m ³ Inhalation 0.31 mg/kg bw/day Oral	
Ethyl acrylate*** 140-88-5		0.92 mg/m ³ (dermal)***		2.5 mg/m ³ (inhalation)***

Predicted No Effect Concentration (PNEC) ***

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
zinc bis[O-(6-methylhept yl)] bis[O-(sec-butyl)] bis(dithiophosphate) *** 93819-94-4	0.004 mg/l fw 0.0046 mg/l mw 0.021 mg/l or	0.0116 mg/kg dw fw 0.00116 mg/kg dw mw	0.00528 mg/kg soil dw		100 mg/l	10.67 mg/kg food
bis(nonylphenyl)ami ne*** 36878-20-3	0.1 mg/l fw 0.01 mg/l mw 1 mg/l or	132000 mg/kg dw fw 13200 mg/kg dw mw	263000 mg/kg dw		1 mg/l	
Ethyl acrylate*** 140-88-5	0.00272 mg/l fw 0.00027 mg/l mw 0.0011 mg/l or***	0.0213 mg/kg sediment dw fw 0.0213 mg/kg sediment dw mw***	1 mg/kg soil dw***		10 mg/l***	0.01 g/kg food***

8.2. Exposure controls**Occupational Exposure Controls**

Version EU



SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Personal Protective Equipment

General Information

If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P2. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.***

Eye Protection

If splashes are likely to occur, wear: Safety glasses with side-shields.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.

Hand Protection

Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

Environmental exposure controls

General Information

The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance		limpid	
Color		No information available	
Physical State @20°C		liquid	
Odor		Characteristic	
Property	Values	Remarks	Method
pH		Not applicable	
Boiling point/boiling range		Not applicable	
Flash point	252 °C 486 °F		Cleveland Open Cup (COC) Cleveland Open Cup (COC)
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Density	853.6 kg/m ³	@ 15 °C	
Water solubility		Insoluble	

Version EU



SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

Solubility in other solvents	No information available	
logPow	No information available	
Autoignition temperature	No information available	
Viscosity, kinematic	56.14 mm2/s 10.35 mm2/s	@ 40 °C @ 100 °C
		ISO 3104 ISO 3104
Explosive properties	Not explosive	
Oxidizing Properties	Not applicable	
Possibility of hazardous reactions	Not applicable	

9.2. Other information

No information available***

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity**General Information** No information available.10.2. Chemical stability**Stability** Stable under recommended storage conditions.10.3. Possibility of hazardous reactions**Hazardous Reactions** None under normal processing.10.4. Conditions to Avoid**Conditions to Avoid** Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.10.5. Incompatible Materials**Materials to Avoid** Strong oxidizing agents.10.6. Hazardous Decomposition Products**Hazardous Decomposition Products** None under normal use.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effectsAcute toxicity Local effects Product Information**Skin contact** . Not classified.**Eye contact** . Severely irritating to eyes.***

Version EU



SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

Inhalation	. Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	. Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy paraffinic***	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)***	LD50 2600 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit - OECD 402)	
bis(nonylphenyl)amine***	LD50 > 5000 mg/kg (Rat - OECD 401)***	LD50 > 2000 mg/kg (Rat - OECD 402) ***	
Ethyl acrylate***	LD50 1120 mg/kg bw (rat)***	LD50 3049 mg/kg bw (rat)***	LC50 (4h) < 9.137 mg/l (rat - vapour)***

Sensitization

Sensitization Not classified as a sensitizer.

Specific effects

Carcinogenicity This product is not classified carcinogenic. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

Chemical Name	European Union
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	-

Mutagenicity This product is not classified as mutagenic.
Reproductive toxicity This product does not present any known or suspected reproductive hazards.

Repeated Dose Toxicity

Subchronic toxicity No information available.

Target Organ Effects (STOT)

Target Organ Effects (STOT) No information available.

Other information

Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

Section 12: ECOLOGICAL INFORMATION**12.1. Toxicity**

Not classified.

Version EU



SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)***	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** 93819-94-4	EbC50 (96h) 2.1 mg/l Selenastrum capricornutum (OECD 201)	EL50 (48h) 5.4 mg/l Daphnia magna (OECD 202)	LC50 (96h) 4.5 mg/l Oncorhynchus mykiss (OECD 203)	
bis(nonylphenyl)amine*** 36878-20-3	EC50 (72h) > 100 mg/l (Desmodesmus subspicatus - OECD 201)***	EC50 (48h) > 100 mg/l (Daphnia magna - OECD 202)***	LC50 (96h) > 100 mg/l (Brachydanio rerio - OECD 203)***	
Ethyl acrylate*** 140-88-5	EC50 (72h) 5.9 mg/l (Pseudokirchnerella subcapitata - OECD 201) EC50 (96h) 5.2 mg/l (Pseudokirchnerella subcapitata - OECD 201) EC50 (72h) 2.65 mg/l (Pseudokirchnerella subcapitata - OECD 201) EC50 (72h) 48 mg/l (Desmodesmus subspicatus)***	EC50 (48h) 7.9 mg/l (Daphnia magna)***	LC50 (96h) 2 mg/l (Cyprinodon variegatus) LC50 (96h) 4.6 mg/l (Oncorhynchus mykiss (96h) LC50 (96h) 2.31 - 2.7 mg/l (Pimephales promelas) LC50 (96h) 10.0 - 22.0 mg/l (Leuciscus idus)***	

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)***	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Ethyl acrylate*** 140-88-5	NOEC (96h) < 3.8 mg/l (Pseudokirchnerella subcapitata - OECD 201) NOEC (96h) < 1.8 mg/l (Pseudokirchnerella subcapitata - OECD 201)***	NOEC (21d) 0.19 mg/l (Daphnia magna) LOEC (21d) 0.45 mg/l (Daphnia magna) EC (21d) 0.5 mg/l (Daphnia magna)***	NOEC (96h) 0.62 mg/l (Cyprinodon variegatus)***	

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability

Version EU



SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

General Information

No information available.

12.3. Bioaccumulative potential**Product Information** No information available.**logPow** No information available**Component Information**

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic*** - 64742-54-7	-
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** - 93819-94-4	0.9
bis(nonylphenyl)amine*** - 36878-20-3	7.7***

12.4. Mobility in soil**Soil** Given its physical and chemical characteristics, the product generally shows low soil mobility.**Air** Loss by evaporation is limited.**Water** Insoluble. The product spreads on the surface of the water.12.5. Results of PBT and vPvB assessment**PBT and vPvB assessment** No information available.12.6. Other adverse effects**General Information** No information available.**Section 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods

Waste from Residues / Unused Products Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

EWC Waste Disposal No. The following Waste Codes are only suggestions: 13 02 05. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

Version EU



SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

Section 14: TRANSPORT INFORMATION

ADR/RID Not regulatedIMDG/IMO Not regulatedICAO/IATA Not regulatedADN Not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

International Inventories No information available***

Further information

No information available***

15.2. Chemical Safety Assessment**Chemical Safety Assessment** No information available

Section 16: OTHER INFORMATION

Full text of R-phrases referred to under sections 2 and 3

R53 - May cause long-term adverse effects in the aquatic environment

R51 - Toxic to aquatic organisms

R41 - Risk of serious damage to eyes

R38 - Irritating to skin***

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment***



SDS # : 081831

QUARTZ INEO HKS D 5W-30

Revision Date: 2015-03-31

Version 2

Full text of H-Statements referred to under sections 2 and 3

H335 - May cause respiratory irritation
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H317 - May cause an allergic skin reaction
 H302 - Harmful if swallowed
 H312 - Harmful in contact with skin
 H331 - Toxic if inhaled
 H412 - Harmful to aquatic life with long lasting effects
 H225 - Highly flammable liquid and vapor
 H413 - May cause long lasting harmful effects to aquatic life
 H318 - Causes serious eye damage
 H411 - Toxic to aquatic life with long lasting effects***

Abbreviations, acronyms

Legend Section 8

TWA: Time Weight Average

STEL: Short Time Exposure Limit

+ Sensitizer

** Hazard Designation

M: Mutagen

*

C:

R:

Skin designation

Carcinogen

Toxic to reproduction

Revision Date: 2015-03-31

Revision Note *** Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet

Version EU